



CHEMISTRY BETWEEN US

PL 44-190 Knurów, ul. Przemysłowa 22, phone: +48 32 335 79 00, e-mail: firma@aibsc.com.pl

Integra B2

Aluminium butyl tape B2 – tape coated with a layer of aluminium on one side and butyl on the other side. It is an ideal solution for internal seals, for example, in aluminium structures, conservatories, etc. When installing windows and doors, which have high requirements for air tightness, the film can be used interchangeably with B1 film.

Specifications – Aluminium butyl tape B2

Property	Standard	Results	
Water tightness	EN 1027	class 9A	own testing
Vapour permeability	EN 12572	Sd ≥ 1500 m	
Flammability class	EN 13501-1	E	own testing
Adhesion of butyl	EN 1939	2 N/mm	
Tensile strength	EN 12311-3	≥ 3 Mpa	
Tear strength	EN 12311-3	≥ 30%	
Air permeability	EN 1026	class 4	own testing
Shelf life		1 year	Storage in a dry place at a temperature of +1 to +25°C

Available widths	50 mm	70 mm	100 mm
Package – quantity per box	1 roll	1 roll	1 roll
Quantity per pallet	144 rolls	144 rolls	120 rolls
Application temperature from +5 to +35°C			