



CHEMISTRY BETWEEN US

PL 44-190 Knurów, ul. Przemysłowa 22, phone: +48 32 335 79 00, e-mail: firma@aibsc.com.pl

Integra Chrome

Integra Chrome – compressed and impregnated multi-purpose tape used for the insulation of the connection between the window and the wall. This product fully eliminates the need for traditional PU foam, meeting all the requirements for a proper and tight window assembly system.

The product is available in a combination of widths and thicknesses, which allows its use in virtually any grout, in connection with all thicknesses of window profiles. Installation itself is very simple and clean, which has a large impact on the aesthetics of the connection. The product is supplied in rolls with the adhesive layer on one side of the tape. Integra Chrome is available in one colour combination: grey/black. The tape should be mounted with the grey part to the inside, and the black side facing outside. Each package contains more detailed installation instructions.



Specifications – Integra Chrome

Property	Standard	Results	
Water tightness	EN 1027	Class 9A	own testing
Vapour permeability	EN 12572	Sd tighter on the inside than on the outside	
Flammability class	EN 13501-1	E	
Thermal conductivity coefficient	EN 12667	$\lambda \leq 0,0428$ W/m*K	
Air permeability	EN 1026	Class 4	
Shelf life		1 year	Storage in a dry place at a temperature of +1 to +25°C

Available widths	64 mm	74 mm	84 mm
Package – quantity per box	4 rolls	4 rolls	3 rolls
Application temperature from +5 to +35°C	Pre-cool the product at a temperature of above 20 degrees		

